



MOD.	LENGHT FT - MT	TENSION CLASS	POWER AT 60% CO ₂ - MIX	COOLING
B4110	10 - 3.0	L	200 A - 180 A	AIR
B4112	12 - 4.0		200 A - 180 A	
B4115	15 - 4.5		200 A - 180 A	

ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
------	---------	-------------	---------------	------


COAXIAL CABLE STANDARD

14.4110AE	TORCIA BND 200 - 180A 10 ft - mt.3	- MIG TORCH BND 200 - 180A 10 ft - mt. 3	4E210AE	1
14.4112AE	TORCIA BND 200 - 180A 12 ft - mt.4	- MIG TORCH BND 200 - 180A 12 ft - mt. 4	4E212AE	1
14.4115AE	TORCIA BND 200 - 180A 15 ft - mt.4,5	- MIG TORCH BND 200 - 180A 15 ft - mt. 4,5	4E215AE	1

COAXIAL CABLE MADE IN USA

14.4110AEU	TORCIA BND 200 - 180A USA 10 ft. mt.3	- MIG TORCH BND 200 - 180A USA 10 ft. - mt.3	4E210AE	1
14.4112AEU	TORCIA BND 200 - 180A USA 12 ft. mt.4	- MIG TORCH BND 200 - 180A USA 12 ft. - mt.4	4E212AE	1
14.4115AEU	TORCIA BND 200 - 180A USA 15 ft. mt.4,5	- MIG TORCH BND 200 - 180A USA 15 ft. - mt.4,5	4E215AE	1

1	14.02.23.13	Ugello OT Ø 13 mm. 1/2"	- Conical gas nozzle OT Ø 13 mm. - 1/2"	4392	25
	14.02.23.16	Ugello OT Ø 16 mm. 5/8"	- Conical gas nozzle OT Ø 16 mm. - 5/8"	4391	25
	14.02.23.16CU	Ugello CU Ø 16 mm. 5/8"	- Conical gas nozzle CU Ø 16 mm. - 5/8"	4393	10

2	14.01.23.08	Punta guidafile Ø 0,8 - 8 x 32	- Contact tip Ø 0,8 - 8 x 32	7488	100
	14.01.23.09	Punta guidafile Ø 0,9 - 8 x 32	- Contact tip Ø 0,9 - 8 x 32	7489	100
	14.01.23.10	Punta guidafile Ø 1,0 - 8 x 32	- Contact tip Ø 1,0 - 8 x 32	7496	100
	14.01.23.12	Punta guidafile Ø 1,2 - 8 x 32	- Contact tip Ø 1,2 - 8 x 32	7490	100
	14.01.23.14	Punta guidafile Ø 1,4 - 8 x 32	- Contact tip Ø 1,4 - 8 x 32	7498	100

3	14.05.23	Diffusore Gas	- Gas diffuser	4335	25
	14.05.23.1	O-RING	- O-RING	7126	10

4	14.03.23	Isolante battuta ugello	- Insulator	4323	10
---	----------	-------------------------	-------------	------	----

5	6	14.06.23	Lancia	- Swan neck	4786	1
		14.061.25	Isolante per lancia	- Swan neck insulator	4780	10

7	14.102.S	Corpo torcia 180 A	- Torch body 180 A	4213B	1
---	----------	--------------------	--------------------	-------	---

8	14.102.1	Dado corpo torcia	- Nut for torch body	4305	1
---	----------	-------------------	----------------------	------	---

ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
9	14.09.23	Interruttore completo - Complete trigger switch	5662	5
10	14.08.23	Impugnatura con viti - Handle with screw	4208	1
	14.08.23.01	Vite e controvite di ricambio - Replacement screw kit		20
10a	14.142	Snodo con molla anteriore - Joint with spring		1
11	14.20.18.10	Cavo assemblato BND 200-180A 10 ft. - Assembled cable BND 200-180A 10 ft.		
	14.20.18.12	Cavo assemblato BND 200-180A 12 ft. - Assembled cable BND 200-180A 12 ft.		
	14.20.18.15	Cavo assemblato BND 200-180A 15 ft. - Assembled cable BND 200-180A 15 ft.		
	14.20.18.10U	Cavo assemblato BND 200-180A USA 10 ft. - Assembled cable BND 200-180A USA 10 ft.		
	14.20.18.12U	Cavo assemblato BND 200-180A USA 12 ft. - Assembled cable BND 200-180A USA 12 ft.		
	14.20.18.15U	Cavo assemblato BND 200-180A USA 15 ft. - Assembled cable BND 200-180A USA 15 ft.		
	14.20.18.10C	Cavo completo BND 200 - 180A 10 ft. - Complete assembled cable BND 200-180A 10ft.		
	14.20.18.12C	Cavo completo BND 200 - 180A 12 ft. - Complete assembled cable BND 200-180A 12ft.		
	14.20.18.15C	Cavo completo BND 200 - 180A 15 ft. - Complete assembled cable BND 200-180A 15ft.		
	14.20.18.10CU	Cavo completo BND 200 - 180A USA 10 ft. - Complete assembled cable BND 200-180A USA 10ft.		
	14.20.18.12CU	Cavo completo USA BND 200 - 180A 12 ft. - Complete assembled cable BND 200-180A USA 12ft.		
14.20.18.15CU	Cavo completo USA BND 200 - 180A 15 ft. - Complete assembled cable BND 200-180A USA 15ft.			
12	VA.A96/P	Faston maschio cilindrico - Faston male		
	VA.B1820	Manicotto - Sleeve		
	VA.RCBN23	Raccordo cavo BND 200 - Coax-cable fitting BND 200		
13	02.30.01	Mollone posteriore - Cable support spring		
	02.30.02	Manicotto per mollone - Cable protector grommet		
14	02.30.03	Scatola posteriore - Connector case		
	02.30.091	Vite per scatola posteriore - Screw		
15	02.30.04	Ghiera - Nut		
16	14.30.BN	Corpo torcia BND - EURO connector BND SPRING PINS		
	13.30.08.1	Spinetta maschio mobile - SPRING PIN		
	02.30.08	O-RING - O-RING		
17	14.04.23	Guaina guidafilo nera Ø 0,8 -1,0 mm. 4,5 mt. - Wire conduit Black Ø 0,8 -1,0 mm. 4,5 mt.	43115	
	14.04.45.01	O-RING - O-RING		
	14.04.AL	Guaina guidafilo per alluminio 4,5 mt. - Wire conduit for aluminium 4,5 mt.		
	14.04.ALT	Capocorda per guaina in alluminio - Nut conduit for aluminium		