

TENSION CLASS	POWER AT 60% CO <sub>2</sub> - MIX	COOLING
L	320 A - 250 A	AIR
	320 A - 250 A	
	320 A - 250 A	

CE	CODE	DESCRIPTION	ORIGINAL REF.
<b>COAXIAL CABLE STANDARD</b>			
	01.330 MK	TORCIA TW3 - MK 10 ft. - mt. 3	310 - 116
	01.340 MK	TORCIA TW3 - MK 12 ft. - mt. 4	312 - 116
	01.345 MK	TORCIA TW3 - MK 15 ft. - mt. 4,5	315 - 116
	01.330 TWE	TORCIA TW3 - EURO Spring Pins 10 ft. - mt. 3	310 - 116 E
	01.340 TWE	TORCIA TW3 - EURO Spring Pins 12 ft. - mt. 4	312 - 116 E
	01.345 TWE	TORCIA TW3 - EURO Spring Pins 15 ft. - mt. 4,5	315 - 116 E
<b>COAXIAL CABLE MADE IN USA</b>			
	01.330 MKU	TORCIA TW3 cavo USA - MK 10 ft. - mt. 3	310 - 116
	01.340 MKU	TORCIA TW3 cavo USA - MK 12 ft. - mt. 4	312 - 116
	01.345 MKU	TORCIA TW3 cavo USA - MK 15 ft. - mt. 4,5	315 - 116
	01.330 TWEU	TORCIA TW3 cavo USA - EURO Spring Pins 10 ft. - mt. 3	310 - 116 E
	01.340 TWEU	TORCIA TW3 cavo USA - EURO Spring Pins 12 ft. - mt. 4	312 - 116 E
	01.345 TWEU	TORCIA TW3 cavo USA - EURO Spring Pins 15 ft. - mt. 4,5	315 - 116 E

**TW3**


14H STD	Part No	Serie 14H STD	PACK
	01.14H30	Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35	Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40	Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45	Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52	Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116	Punta Ø 1,6 - Contact tip Ø 1,6	100

14 Ø 6,3	Part No	Serie 14 Ø 6,3 serie Uso Leggero	PACK
	01.14.30	Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14.35	Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14.40	Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14.45	Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14.52	Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14.116	Punta Ø 1,6 - Contact tip Ø 1,6	100

14H SPECIAL CU-AG	Part No	Serie 14H SPECIAL CU-AG	PACK
	01.14H30AG	Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35AG	Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40AG	Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45AG	Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52AG	Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116AG	Punta Ø 1,6 - Contact tip Ø 1,6	100

14H NICKEL PLATED	Part No	Serie 14H Nichelate	PACK
	01.14H30N	Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35N	Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40N	Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45N	Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52N	Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116N	Punta Ø 1,6 - Contact tip Ø 1,6	100

ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
	01.23.37	Ugello gas isolato Ø 9,5 mm. - Insulated gas nozzle Ø 9,5 mm.	23 - 37	25
	01.23.50	Ugello gas isolato Ø 13 mm. - Insulated gas nozzle Ø 13 mm.	23 - 50	25
	01.23.62	Ugello gas isolato Ø 16 mm. - Insulated gas nozzle Ø 16 mm.	23 - 62	25
	01.23.75	Ugello gas isolato Ø 19 mm. - Insulated gas nozzle Ø 19 mm.	23 - 75	25
	01.34CT	Boccola isolante - CT PASSO LARGO - Coarse thread insulated - CT	34CT	25
	01.34FN	Boccola isolante - FN PASSO FINE - Fine thread insulated - FN	34FN	25
	01.24CT50	Ugello gas Ø 13 mm. PASSO LARGO - Gas nozzle CT Ø 13 mm.	24CT50S	25
	01.24CT62	Ugello gas Ø 16 mm. PASSO LARGO - Gas nozzle CT Ø 16 mm.	24CT62S	50
	01.24CT75	Ugello gas Ø 19 mm. PASSO LARGO - Gas nozzle CT Ø 19 mm.	24CT75S	25
	01.24FN50	Ugello gas Ø 13 mm. PASSO FINE - Gas nozzle FN Ø 13 mm.	24FN50S	25
	01.24FN62	Ugello gas Ø 16 mm. PASSO FINE - Gas nozzle FN Ø 16 mm.	24FN62S	50
01.24FN75	Ugello gas Ø 19 mm. PASSO FINE - Gas nozzle FN Ø 19 mm.	24FN75S	25	
	01.54A	Diffusore gas - Gas diffuser	54A	50
	01.24A50	2a Ugello gas ad innesto Ø 13 mm. - Nozzle adjustable Ø 13 mm.	24A50	25
	01.24A62	2a Ugello gas ad innesto Ø 16 mm. - Nozzle adjustable Ø 16 mm.	24A62	25
	01.24A75	2a Ugello gas ad innesto Ø 19 mm. - Nozzle adjustable Ø 19 mm.	24A75	25
	01.34A	3a Boccola isolante - Adjustable nozzle insulator	34A	25

ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
6	01.63A45	Lancia 45°	- Complete torch head 45°	63A45
	01.63A60	Lancia 60°	- Complete torch head 60°	63A60
	01.64N	Convogliatore gas	- Gas hose nipple	64N
	01.74A	Copertura isolante	- Conductor tube insulation (rubber)	74A
7	01.83	Impugnatura	- Handle case	83
	01.92	Interruttore completo	- Trigger switch w/switch blades	92
	01.92C	Coppia lamelle	- Switch blades set	92C
8	01.122	Vite per impugnatura	- Screw	10
9	01.102	Corpo torcia	- Cable connector block w/screws and separator	102
	01.12M	Grano fissacavo	- Cable connector block screw	10M
	01.112	Cavallotto separatore	- Separator	112
10	01.142.6	Supporto protettivo cavo anteriore	- Cable support front	142 - 6
11	01.244	Faston		
	VA.FS.3B	Fascetta stringicavo superiore	- Clamp	
	VA.A96/P	Faston maschio cilindrico	- Faston male	
13	01.20.300 T	Cavo coassiale TW3-300A-35 mmq	- Replacement cable TW3-300A-35 mmq	per mt.
	01.20.300U	Cavo coassiale USA TW3-300A-35 mmq	- Replacement cable USA TW3-300A-35 mmq	per mt.
14	01.42.4045	Guaina guidafilo Ø 1,7 wire Ø 0,8 / 1,0 mt.4,2	- Liner Ø 1,7 wire Ø 0,8 / 1,0 mt.4,2	
	01.42.4045.5	Guaina guidafilo Ø 1,7 wire Ø 0,8 / 1,0 mt.5	- Liner Ø 1,7 wire Ø 0,8 / 1,0 mt.5	
	01.42.4045.7	Guaina guidafilo Ø 1,7 wire Ø 0,8 / 1,0 mt.7	- Liner Ø 1,7 wire Ø 0,8 / 1,0 mt.7	
	02.30.08	O - RING	- O - RING	43B
	01.44.116	Guaina guidafilo Ø 2,1 wire Ø 1,0 / 1,6 mt.4,5	- Liner Ø 2,1 wire Ø 1,0 / 1,6 mt.4,5	44 - 116
	01.44.116.5	Guaina guidafilo Ø 2,1 wire Ø 1,0 / 1,6 mt.5	- Liner Ø 2,1 wire Ø 1,0 / 1,6 mt.5	
14a	01.04.MKAL	Guaina guidafilo per alluminio	- Liner for Aluminium	
	01.04. MKALT	Capocorda	- Nut for liner for Aluminium	
	02.30.08	O - RING	- O - RING	43 B
15	01.30.01G	Mollone posteriore	- Cable support spring	
16	01.30.03T	Scatola posteriore tonda	- Connector case	
17	01.224	O - RING	- Connector plug O - RING	224
	01.30.174	Connessione posteriore MK	- Central Connector MK	

### TW 3 EURO CONNECTION

18				
11a	01.20.310TWE	Cavo assemblato 10 ft. EURO Ø 12x1	- Assembled replacement cable 10 ft. EURO Ø 12x1	
	01.20.312TWE	Cavo assemblato 12 ft. EURO Ø 12x1	- Assembled replacement cable 12 ft. EURO Ø 12x1	
19	01.20.315TWE	Cavo assemblato 15 ft. EURO Ø 12x1	- Assembled replacement cable 15 ft. EURO Ø 12x1	
	01.20.310TWEU	Cavo assemblato USA 10 ft. EURO Ø 12x1	- Assembled replacement cable USA 10 ft. EURO Ø 12x1	
20	01.20.312TWEU	Cavo assemblato USA 12 ft. EURO Ø 12x1	- Assembled replacement cable USA 12 ft. EURO Ø 12x1	
	01.20.315TWEU	Cavo assemblato USA 15 ft. EURO Ø 12x1	- Assembled replacement cable USA 15 ft. EURO Ø 12x1	
21	VA.A96/P	Faston maschio cilindrico	- Faston male	
	VA.B2022	Manicotto	- Sleeve	
22	01.20.01	Dado Ø 12 x 1 mm.	- Nut Ø 12 x 1 mm.	
	01.20.03	Raccordo Ø 12x1 mm	- Coax-cable fitting Ø 12x1 mm	
23	01.30.01G	Mollone posteriore	- Cable support spring	
24	01.30.03T	Scatola posteriore tonda	- Connector case	
	02.30.04	Ghiera	- Nut	
25	01.30.05	Corpo torcia Ø 12 x 1mm	- EURO connector TW-E spring pins Ø12 x 1mm	
	VA.A69/P	Faston femmina cilindrico	- Faston female	
	02.30.08	O - RING	- O - RING	
26	01.30.06	Dado	- Liner nut	
27	13.30.08.1	Spinetta maschio mobile	- Spring pin	