



TENSION CLASS	POWER AT 60% CO <sub>2</sub> - MIX	COOLING
L	400 A - 360A	AIR
	400 A - 360 A	
	400 A - 360 A	

CODE	DESCRIPTION	ORIGINAL REF.
<b>COAXIAL CABLE STANDARD</b>		
01.430 MK	TORCIA TW4 - MK 10 ft. - mt. 3	410 - 116
01.440 MK	TORCIA TW4 - MK 12 ft. - mt. 4	412 - 116
01.445 MK	TORCIA TW4 - MK 15 ft. - mt. 4,5	415 - 116
01.430 TWE	TORCIA TW4 - EURO Spring Pins 10 ft. - mt. 3	410 - 116 E
01.440 TWE	TORCIA TW4 - EURO Spring Pins 12 ft. - mt. 4	412 - 116 E
01.445 TWE	TORCIA TW4 - EURO Spring Pins 15 ft. - mt. 4,5	415 - 116 E
<b>COAXIAL CABLE MADE IN USA</b>		
01.430 MKU	TORCIA TW4 cavo USA - MK 10 ft. - mt. 3	410 - 116
01.440 MKU	TORCIA TW4 cavo USA - MK 12 ft. - mt. 4	412 - 116
01.445 MKU	TORCIA TW4 cavo USA - MK 15 ft. - mt. 4,5	415 - 116
01.430 TWEU	TORCIA TW4 cavo USA - EURO Spring Pins 10 ft. - mt. 3	410 - 116 E
01.440 TWEU	TORCIA TW4 cavo USA - EURO Spring Pins 12 ft. - mt. 4	412 - 116 E
01.445 TWEU	TORCIA TW4 cavo USA - EURO Spring Pins 15 ft. - mt. 4,5	415 - 116 E

**TW4**

Part No	Serie 14H STD	PACK
1	01.14H30 Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35 Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40 Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45 Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52 Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116 Punta Ø 1,6 - Contact tip Ø 1,6	100

  

Part No	Serie 14 e 6,3 serie Uso Leggero	PACK
1	01.14.30 Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14.35 Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14.40 Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14.45 Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14.52 Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14.116 Punta Ø 1,6 - Contact tip Ø 1,6	100

Part No	Serie 14H SPECIAL CU-AG	PACK
1	01.14H30AG Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35AG Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40AG Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45AG Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52AG Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116AG Punta Ø 1,6 - Contact tip Ø 1,6	100

  

Part No	Serie 14H Nichelate	PACK
1	01.14H30N Punta Ø 0,8 - Contact tip Ø 0,8	100
	01.14H35N Punta Ø 0,9 - Contact tip Ø 0,9	100
	01.14H40N Punta Ø 1,0 - Contact tip Ø 1,0	100
	01.14H45N Punta Ø 1,2 - Contact tip Ø 1,2	100
	01.14H52N Punta Ø 1,4 - Contact tip Ø 1,4	100
	01.14H116N Punta Ø 1,6 - Contact tip Ø 1,6	100

ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
2	01.23.37	Ugello gas isolato Ø 9,5 mm.	23 - 37	25
	01.23.50	Ugello gas isolato Ø 13 mm.	23 - 50	25
	01.23.62	Ugello gas isolato Ø 16 mm.	23 - 62	25
	01.23.75	Ugello gas isolato Ø 19 mm.	23 - 75	25
4	01.34CT	Boccola isolante - CT PASSO LARGO	34CT	25
	01.34FN	Boccola isolante - FN PASSO FINE	34FN	25
	01.24FN50	Ugello gas Ø 13 mm. PASSO FINE	24FN50S	25
	01.24FN62	Ugello gas Ø 16 mm. PASSO FINE	24FN62S	50
	01.24FN75	Ugello gas Ø 19 mm. PASSO FINE	24FN75S	25
	01.24CT50	Ugello gas Ø 13 mm. PASSO LARGO	24CT50S	25
	01.24CT62	Ugello gas Ø 16 mm. PASSO LARGO	24CT62S	50
01.24CT75	Ugello gas Ø 19 mm. PASSO LARGO	24CT75S	25	
2a	01.24A50	Ugello gas ad innesto Ø 13 mm.	24A50	25
	01.24A62	Ugello gas ad innesto Ø 16 mm.	24A62	25
	01.24A75	Ugello gas ad innesto Ø 19 mm.	24A75	25
	01.34A	Boccola isolante	34A	25
5	01.54A	Diffusore gas	54 A	50
	FM 54 M8	Diffusore gas M8 L=42		
6	01.64A45	Lancia 45°	64A45	
	01.64A60	Lancia 60°	60A60	
	01.64N	Convogliatore gas	64N	
	01.74A	Copertura isolante	74A	10



ITEM	Part No	DESCRIPTION	ORIGINAL REF.	PACK
7	01.84	Impugnatura	- Handle case	84
	01.94	Interruttore completo	- Trigger switch w/switch blades	94
	01.92C	Coppia lamelle	- Switch blades set	92C
8	01.122	Vite per impugnatura	- Screw	10
9	01.104	Corpo torcia	- Cable connector block w/screws and separator	104
	01.114	Cavallotto separatore	- Separator	114
	01.14M	Grano fissacavo	- Cable connector block screw	14M
10	01.144.6	Supporto protettivo cavo anteriore	- Cable support front	144 - 6
11	01.244	Faston	- Faston	
	VA.FS.3B	Fascetta stringicavo superiore	- Clamp	
	VA.A96/P	Faston maschio cilindrico	- Faston male	
13	01.20.400 T	Cavo coassiale TW4 -400A-50 mmq	- Replacement cable TW4 -400A-50 mmq	per mt.
	01.20.400U	Cavo coassiale USA TW4 -400A-50 mmq	- Replacement cable USA TW4 -400A-50 mmq	per mt.
14	01.44.116	Guaina guidafilo Ø 1,0 / 1,6 mt.4,2	- Liner Ø 2,1 wire Ø 1,0 / 1,6 mt.4,2	44 - 116
	01.44.116.5	Guaina guidafilo Ø 1,0 / 1,6 mt.5	- Liner Ø 2,1 wire Ø 1,0 / 1,6 mt.5	
	01.44.116.7	Guaina guidafilo Ø 1,0 / 1,6 mt.7	- Liner Ø 2,1 wire Ø 1,0 / 1,6 mt.7	
	01.44.564	Guaina guidafilo Ø 1,6 / 2,0 mt.4,5	- Liner Ø 2,6 wire Ø 1,6 / 2,0 mt.4,5	44 - 564
	01.44.564.7	Guaina guidafilo Ø 1,6 / 2,0 mt.7	- Liner Ø 2,6 wire Ø 1,6 / 2,0 mt.7	
	02.30.08	O - RING	- O - RING	
14a	01.04.MKAL	Guaina guidafilo per alluminio mt. 4,5	- Liner for Aluminium mt. 4,5	
	01.045.MKAL	Guaina guidafilo per alluminio mt. 5,5	- Liner for Aluminium mt. 5,5	
	01.04.MKALT	Capocorda	- Nut for liner for Aluminium	
	02.30.08	O - RING	- O - RING	43 B
15	01.30.01G	Mollone posteriore	- Cable support spring	
16	01.30.03T	Scatola posteriore tonda	- Connector case	
17	01.224	O - RING	- Connector plug O - RING	224
	01.30.174	Connessione posteriore MK	- Central Connector MK	

## TW4 EURO CONNECTION

18	01.20.410TWE	Cavo assemblato 10 ft. EURO Ø 12x1	- Assembled replacement cable 10 ft. EURO Ø 12x1	
	01.20.412TWE	Cavo assemblato 12 ft. EURO Ø 12x1	- Assembled replacement cable 12 ft. EURO Ø 12x1	
	01.20.415TWE	Cavo assemblato 15 ft. EURO Ø 12x1	- Assembled replacement cable 15 ft. EURO Ø 12x1	
	01.20.410TWEU	Cavo assemblato USA 10 ft. EURO Ø 12x1	- Assembled replacement cable USA 10 ft. EURO Ø 12x1	
	01.20.412TWEU	Cavo assemblato USA 12 ft. EURO Ø 12x1	- Assembled replacement cable USA 12 ft. EURO Ø 12x1	
	01.20.415TWEU	Cavo assemblato USA 15 ft. EURO Ø 12x1	- Assembled replacement cable USA 15 ft. EURO Ø 12x1	
19	VA.A96/P	Faston maschio cilindrico	- Faston male	
	VA.B2022	Manicotto	- Sleeve	
20	01.20.01	Dado Ø 12 x 1 mm.	- Nut Ø 12 x 1 mm.	
	01.20.03	Raccordo Ø 12x1	- Coax-cable fitting Ø 12x1	
21	01.30.01G	Mollone posteriore	- Cable support spring	
22	01.30.03T	Scatola posteriore tonda	- Connector case	
	02.30.04	Ghiera	- Nut	
23	01.30.05	Corpo torcia Ø 12 x 1mm	- EURO connector TW-E spring pins Ø 12 x 1mm	
	VA.A69/P	Faston femmina cilindrico	- Faston female	
	02.30.08	O - RING	- O - RING	
24	01.30.06	Dado	- Liner nut	
25	13.30.08.1	Spinetta maschio mobile	- Spring pin	